

| |
|-----------------------|
| MSDS NUMBER W-3045 |
|-----------------------|

| | | |
|------------------------------------|-------------------------|--------------------------|
| EMERGENCY TELEPHONE NUMBERS | COMPANY 405-665-6565 | CHEMTREC 800/424-9300 |
|------------------------------------|-------------------------|--------------------------|

I. PRODUCT IDENTIFICATION

| | | | |
|--|--|----------------|----------------------|
| PRODUCT ULTRA LOW SULFUR DIESEL FUEL | CHEMICAL NAME AND SYNONYMS Petroleum Hydrocarbon Mixture, Distillate, | | |
| CHEMICAL FAMILY Petroleum Hydrocarbon Distillate | FORMULA C11 - C20 | | |
| National Fire Protection Association Hazard Rating Codes Least - 0 Slight - 1 Moderate - 2 High - 3 Extreme - 4 | HEALTH CODE 0 | FIRE CODE 2 | REACTIVITY CODE 0 |

II. SUMMARY OF HAZARDS

CAUTION! COMBUSTIBLE LIQUID AND VAPOR. HARMFUL IF INHALED AND MAY CAUSE DELAYED LUNG INJURY. CAN CAUSE NERVOUS SYSTEM DEPRESSION. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Keep away from heat and flame. Avoid breathing vapor. Use ventilation adequate to keep vapor below recommended exposure limits. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

NIOSH, EPA, & current literature have indicated that breathing whole diesel exhaust over a working lifetime may cause cancer in humans. Animals exposed to whole diesel exhaust over a lifetime have developed lung tumors (cancer). Diesel exhaust may cause eye irritation, headache, light-headedness, nausea, vomiting, heartburn, weakness, numbness, tingling in the extremities, chest tightness and wheezing. Cough and labored breathing have been reported in garage workers without adequate ventilation (air circulation) in the garage.

| | | |
|-------------------------------|---|---|
| DOT Hazardous Material YES | DOT SHIPPING NAME AND NUMBER Diesel Fuel, 3, NA1993, III | DOT HAZARD CLASS 3 (Flammable Liquid) |
|-------------------------------|---|---|

III. HAZARDOUS COMPONENTS

| INGREDIENT | % RANGE | PEL/TLV | HAZARD |
|--|-------------|---------------------------------------|---|
| Straight Run Middle Distillate (CAS # 64741-44-2) | 60 to 100 % | Petroleum Distillate TWA - 400 ppm | Combustible Acute Health Chronic Health |
| Light Catalytic Cracked Distillate (CAS # 64741-59-9) | 0 to 40 % | Petroleum Distillate TWA - 400 ppm | |

Diesel exhaust contains: Nitrogen Dioxide, Sulfuric Acid, Sulfur Dioxide, Aliphatic Aldehydes, Soot containing Polynuclear Aromatic Hydrocarbons, Carbon Monoxide, Hydrogen Sulfide.

IV. HEALTH INFORMATION

| EXPOSURE BY ROUTE OF ENTRY | EXPOSURE CHARACTERISTICS AND FIRST AID | |
|----------------------------|--|--|
| INHALATION | EFFECTS | Acute: Headache, nasal and respiratory irritation, nausea, drowsiness, breathlessness, fatigue, central nervous system depression, convulsions, and loss of consciousness. |
| | FIRST AID | Move exposed person to fresh air. If breathing has stopped, perform artificial respiration. Get medical attention as soon as possible. |
| SKIN | EFFECTS | Acute: irritation Chronic: dermatitis |
| | FIRST AID | If clothing soaked, immediately remove clothing and wash skin with soap and water. Launder clothing before wearing. Get medical attention promptly. |
| EYES | EFFECTS | Acute: irritation |
| | FIRST AID | Immediately flush eyes with water for a minimum of 15 minutes, occasionally lifting the lower and upper lids. Get medical attention promptly. |
| SWALLOWING INGESTION | EFFECTS | Acute: aspiration hazard, headache, nausea, drowsiness, fatigue, pneumonitis, pulmonary edema, central nervous system depression, convulsions and loss of consciousness. |
| | FIRST AID | Call a physician immediately, ONLY induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person |

Medical conditions Generally
Agravated by Exposure

N/AV

| | | |
|--|--|---|
| LISTED AS POTENTIAL CARCINOGEN OR CARCINOGEN | NOT LISTED <u> X </u> INTERNATIONAL Agency for Research on Cancer _____ | NATIONAL TOXICOLOGY PROGRAM _____ OSHA _____ |
|--|--|---|

V. EMPLOYEE PROTECTION

RESPIRATORY PROTECTION (NIOSH APPROVED RESPIRATORS SEE OSHA STD. 1910.134)

Up to 4000 ppm, half-mask organic vapor respirator. Up to 20,000 ppm, full-face organic vapor respirator or full-face supplied air respirator. Greater than 20,000 ppm, fire fighting, or unknown concentration, self-contained breathing apparatus with positive pressure.

| | |
|--|--|
| | EYE Safety glasses, chemical goggles or face shield as appropriate. |
| | SKIN Gloves: Nitrile, neoprene or other material resistant to distillate. |

VENTILATION

Maintain local or dilution ventilation to keep air concentration below 400 ppm. Loading, unloading, tank gauging, etc., remain upwind. Request assistance of safety and industrial hygiene personnel to determine air concentrations.

VI. FIRE PROTECTION INFORMATION

| FLASH POINT AND METHOD | AUTOIGNITION TEMPERATURE ESTIMATED | FLAMMABLE LIMITS % VOLUME IN AIR ESTIMATED | LOWER | UPPER |
|------------------------|------------------------------------|--|-------|-------|
| Tag Closed Cup 130 °F | 490 °F | | 0.7 | 6 |

EXTINGUISHING MEDIA

Carbon dioxide, dry chemical, or foam. Water stream may spread fire, use water spray only to cool containers exposed to fire. If leak or spill has not ignited, use water spray to disperse the vapors.

HAZARDOUS DECOMPOSITION PRODUCTS

Incomplete combustion can yield carbon monoxide and various hydrocarbons.

FIRE AND EXPLOSION HAZARDS

Can form combustible mixtures with air when heated.

STORAGE

Do not store with strong oxidizers. Store as OSHA Class II combustible liquid.

| | |
|---|---|
| HAZARDOUS POLYMERIZATION WILL NOT OCCUR <input checked="" type="checkbox"/> MAY OCC <input type="checkbox"/> | STABILITY STABLE <input checked="" type="checkbox"/> UNSTABLE <input type="checkbox"/> |
|---|---|

VII. PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|---------------------------------------|--|---|
| BOILING POINT 330 - 675 °F | Reid VAPOR PRESSURE (RVP) at 100 °F ESTIMATED less than 0.1 pound | EVAPORATION (ETHYL ETHER = 1) ESTIMATED slower |
| PERCENT VOLATILE BY VOLUME (%) 100 | AVG. MOLECULAR WEIGHT N/A | APPEARANCE May be clear to yellow-brown |
| ODOR Diesel Fuel | DROP POINT Pour Point -25 to +10 °F | ESTIMATED VAPOR DENSITY (AIR = 1) 6 |
| SPECIFIC GRAVITY 0.8 to 0.9 | VISCOSITY 2 to 4 cs at 100°F | SOLUBILITY (G/100g WATER AT 20° C) Negligible |

VIII. ENVIRONMENTAL PROTECTION

| | |
|--|---|
| S P I L L S | Notify emergency response personnel. Evacuate area and remove ignition sources. Build dike to contain flow. Remove free liquid, do not flush to sewer or open water. Pick up with inert absorbent and place in closed container for disposal. |
| D W I A S S P T O E S A L | Utilize licensed waste disposal company. Consider recycling or incineration. Utilize permitted hazardous waste disposal site or industrial waste disposal site as appropriate. |

ADDITIONAL INFORMATION

The following chemicals are subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and reauthorization Act of 1986 and 40 CFR Part 372:

| | | | |
|-------------|----------------|---------------|---------------|
| PREPARED BY | Johnnie L. Ray | DATE PREPARED | July 24, 2006 |
|-------------|----------------|---------------|---------------|

DISCLAIMER

The information and recommendations contained in this publication have been compiled from sources believed to be reliable and to represent the best current opinion on the subject at the time of publication. Since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the recommendations will be adequate for all individuals or situations. Each user of the product described herein should determine the suitability of the described product for his particular purpose and should comply with all federal and state rules and regulations concerning the described product.

ABBREVIATIONS

| | |
|-------|--|
| CAS # | Chemical Abstracts Service Number |
| N/A | Not Applicable |
| N/AV | Not Available |
| ppm | Parts per million |
| PEL | Permissible Exposure Limit |
| TLV | Threshold Limit Value |
| | Both the OSHA PEL and the American Conference of Governmental Industrial Hygienists TLV were reviewed. Where a difference existed, the more restrictive of the two was selected. |
| STEL | Short Term Exposure Limit |
| TWA | Time-Weighted Average |